

CONNEXIONS (UK) PLC

Specification For Approval

5 Core Coax Video Cable

Item		A.Q.L	Description
Conductor	NO./mm	0.16	Stranded tinned Copper
	5 / T0.16 x 7	(+/-0.008)	
Insulation	NO./mm	1.90	Foam PE insulation
	5 / 1.90	(+/-0.13)	
Shield	NO./mm	96 (+/-2)	Stranded cores cable
	5 / T0.10 x 9	0.10 (+/-0.008)	Tinned copper braid shield
Sheath	NO./mm	3.30	Red,green,blue,black,yellow
	5 / 3.30	(+/-0.18)	PVC sheath
Conductor	NO./mm	0.16	Stranded tinned copper
	4 / T0.16 x 7	(+/-0.01)	
Insulation	NO./mm	0.90	Red,green,blue,black
	4 / 0.90 SPE	(+/-0.10)	Solid PE insulation
Drain wire	NO./mm	0.16	Stranded tinned Copper
	1 / T0.16 x 7	(+/-0.01)	
Shield	NO./mm		Stranded cores cable
	Al foil	-----	Al foil spiral shield
Assembly coating	Transparent	Stranded Cores cable , Mylar spiral coating	
Drain wire	NO./mm	0.16	Stranded tinned Copper
	1 / T0.16 x 7	(+/-0.01)	
Shield	NO./mm		Al foil spiral shield
	Al foil	-----	
Jacket	NO./mm	11.10	Black PVC jacket
	11.10	(+/-0.60)	

